COLOR: Print Black

7.27.20

SIZE: 481mm x140mm FINISH: Acordian Fold with fold over cover or Roll Fold with fold over cover

power source, it will take around 6 hours to completely charge the unit. The charging icon on the LED will blink and continue to show capacity until it reaches 100% and shuts off automatically. TO MAKE SURE YOUR CHARGER

Product Features

There are six patents for this product

1. Mini/lightweight/portable/easy storage, it is a necessity for a selfdriving tour & outdoor activities.

IS FULLY CHARGED, CHARGE IT FOR 12 HOURS BEFORE INITIAL USE.

- 2. Multi-function in one product: pressure gauge + air pump + lighting +
- 3. Safety and efficiency with a high-rate lithium polymer battery.
- 4. Eight features to guarantee safety
- 5. Can inflate up to 150PSI with super-powerful inflatable ability
- 6. High-precision tire pressure detection, accurate to 0.01BAR
- 7. Low battery alert function, to make sure your product always has sufficient power

READ AND UNDERSTAND ALL SAFETY INFORMATION BEFORE USING THIS ELECTRICAL SHOCK, EXPLOSION, or FIRE, which may lead to a SERIOUS INJURY, DEATH, or PROPERTY DAMAGE.

ELETCTRICAL SHOCK. Product is an electrical device that can shock and cause serious injury. Do not cut power cords. Do not submerge in water or get wet EXPLOSION. Unmonitored, incompatible, or damaged batteries can explode if used with product. Do not leave product unattended while in use. Do not

attempt to jump start a damaged or frozen battery. Use product only with batteries of recommended voltage. Operate product in well ventilated areas. \\ FIRE. Product is an electrical device that emits heat and is capable of causing burns. Do not cover product. Do not smoke or use any source of electrical spark or fire when operating jump start . Keep product away from

EXPLOSIVE GASES. Working in the vicinity of a lead-acid is dangerous Batteries generate explosive gases during normal battery operation. To reduce risk of battery explosion, follow all safety information instructions and those published by the battery manufacturer and manufacturer of any equipment intended to be used in the vicinity of battery. Review cautionary markings on these products and on engine.

Accessories may present a choking hazard to children. Do not leave children unattended with product or any accessory. The product is not a toy.

Never plug the air tube into any person or animal's mouth/ear/noise/eye. Using near any combustible or explosive liquid or gas place (such as gas station) is forbidden.

The air tube will be really hot after inflation, watch your hand while removing it.

Suggest waiting for 5-10 minutes between inflating each tire . Do not plug in the charging cable for a long time, in case it over charges or

VARRANTY, REGISTRATION & TECHNICAL SUPPORT

PLEASE FILL OUT AND RETURN THE PRODUCT REGISTRATION CARD INCLUDED WITH YOUR NEW ROYAL PRODUCT OR FILL OUT THE PRODUCT REGISTRATION

BE SURE TO KEEP A COPY OF YOUR SALES RECEIPT!

ROYAL CONSUMER INFORMATION PRODUCTS, INC. ("Royal"), at 1011 U.S. Highway 22 west. Suite 202 Bridgewater, NJ 08807 USA WARRANTS that your NEW Product is free of defects of workmanship and materials. If there is a defect or malfunction of this product, Royal will repair it free of charge as

> PARTS: New or comparable rebuilt parts in exchange for defective parts for ONE (1) YEAR from date of customer

LABOR: Royal provides labor warranty for (90) DAYS from date of end-user purchase. Product must be sent postage prepaid and insured to Royal in accordance with the warranty procedures outlined below. At completion of the repair, the consumer will be responsible for the cost for any parts or

This warranty does not apply to persons who purchased this product

This warranty does not include adjustments, parts and/or repairs required by circumstances beyond the control of Royal, including but not limited to fire or other casualty, accident, neglect, abuse, misuse, abnormal use, or battery leakage damages.

THERE ARE NO OTHER EXPRESSED WARRANTIES EXCEPT AS STATED HEREIN.

AFTER THE PERIOD OF EXPRESSED WARRANTY SET FORTH HEREIN, THERE ARE NO EXPRESSED OR IMPLIED WARRANTIES AND THOSE EXCLUDED PURPOSE. Royal shall NOT be held liable for CONSEQUENTIAL DAMAGES resulting from any failure, defect or malfunction of this product. Some States

do not allow limitations on how long an implied warranty lasts and some

States do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you.

WARRANTY PROCEDURES

TO OBTAIN SERVICE UNDER THE TERMS OF THIS WARRANTY Please do the following

1. Send a copy of your original sales receipt showing original purchase date along with your mailing and shipping addresses, the model name of the product, and a note describing the nature of the problem to:

Royal Consumer Information Products, Inc.

Warranty Processing

Easton, PA 18042-7391 USA

Do Not Return the Product to This Address

2. You will receive a return authorization number via U.S Mail within 7-12 business days from the date your return request is received if it is determined that there is a basis for a replacement product. The return charges, if any, and the correct shipping address for the returned product. PRODUCT SUPPORT HOTLINE:

> For questions on use of this product or this warranty call 1-800-272-6229 (in the U.S. and Canada) or in Mexico call 01-800-849-4826, Monday through Friday during normal business hours. You can also e-mail Royal at: hotline@royal.com



WARNING: This product can expose you to chemicals including Phthalates and Total Lead, which is known to e State of California to cause reproductive harn more information go to P65Warnings.ca.gov.

10

To shut off unit, simply press power button for 3 seconds, If unit is ON and

This unit has 4 preset modes to choose from. The 4 modes are "CAR"

You can press @ once to toggle to right mode. A preset pressure value will

This unit has 4 pressure units of measure for your convenience. They are

"PSI" "BAR" "KPA" & "Kg/cm2". You can press

once to toggle to right unit

All preset modes include a predetermined pressure value for your convenience

adjustment. Pressing once will adjust 0.01 value once, holding it will quickly

adjust addtional 0.01 value. Waiting for 3 seconds will set value, or press ⊚ to

However, if you need to fine-tune it, you can press the ⊖or ⊕ for fine

set. Turning the pump on will automatically stop it at the preset point.

of measure. Your choice of unit will reappear on the next power on.

turn back on, simply follow the power on procedures.

"MOTORCYCLE" "BICYCLE" & "BASKETBALL"

be selected but you can adjust it as you see fit.


Value Adjustment $\bigcirc \oplus$

Mode Change (3)

there is no activity for more than 3 minutes, it will shut off automatically. To

JS1000IM0420

ROYAL



- Pressure unit change/Flashlight control
- ⊖ Dial down adjustment Power control/inflator start
- Dial-up adjustment Mode change

- 1. EC5 jump start connector
- 3. Multi information LED
- 4. TYPE C input
- 6. LED flashlight 7. Control buttons

Product Specifications

Storage Temp: -20 - 60° 0

Product dimensions: 150 x 129 x 37mn Charging spec: DC5V/2A

Battery capacity: 8800mAh

Charging port: Type-C

LED Light: 1 LED

Inflator Speed: Car tires up to 18 inch ~ 15 minutes (from empty to full)

Inflator tube: 240mm extension (Including air tap)

Main unit x 1

Carrying bag x 1 AC Charger x 1 Car Charger x 1

USB Cable x 1 Nozzle Kit x 1

User Manual x 1

Jump Starter Cable x 1

Inflator Tube x 1

Instruction Card x 1

Air Pump Operating Instructions

Using the Inflator Pump

equipment, inflatable swimming apparatus, and small air mattresses This product can be operated with manual or preset limits for automatic inflation. Four different units of measure in pressure can be selected for ease of operation. As a side benefit, this product can also be used as a

Most vehicles with inflatable wheels (exclude trucks that are> 5 tons), sports

It comes with 4 preselect modes indicated as CAR, MOTOCYCLE, BICYCLE and BASKETBALL features for a no-guess operation. Once you have selected the mode, you can fine-tune the pressure to fit the applications. Once this is all set, the automatic function will take over with no guesswork. With an added LED, it is perfect for those hard-to-see areas when it is dark.

Car/Motorcycle/Electric Scooter/Bicycle

Press and lock the inflator quick-connect to the tire valve stem. Turn on the main unit, and the LED will display the current tire pressure. Select either manual or preset mode, then inflate to the desired pressure setting.

Inflatable ball/Air floatation equipment/Air mattres

Choose the right plastic inflator adaptor; clip and press into the quick Product offers 4 different units of pressure measurement:

(PSI) / (BAR) / (KPA) / (Kg/cm²)

0.6 BAR

connect. Turn on the main unit, select manual or preset mode, then inflate

Unit Change 🔕

Power ON/OFF (b)

Press power button for 3 seconds, it will turn on, LED will display onboard

This unit has a built in LED flashlight to illuminate it. First you power on the unit, then press ⊗ for 3 seconds, and the LED will turn on. Pressing⊚again will turn it into S.O.S. flash mode. A sustained press will

This unit has a USB outlet 5V/2A to charge up your portable electronics. It has an 8800mAh battery, and it will provide ample charging power to your electronics. To use this feature, all you need to do is

IUMP STARTER OPERATION

The jump-start unit is suitable to diesel 5.0L gasoline or 3.0L diesel engines. (A colder climate or degraded engine system will impact the effectiveness for diesel period.)

When your car is disabled on the road, this jump starter will help you

to get back on the road without calling for heip. Using high output Lithium battery technology, the battery will quickly generate up to 1000A peak current to crank over your disabled engine In order to maximize safety, this unit comes with 8 protection

1. Short circuit 2. Reverse polarity 3. Over-charging 4. Excess current output 5. Excess temperature 6. Overload 7. Low voltage limits 8. Excess voltage limits

Note: Please make sure the unit has more than 30% of battery capacity remaining





Charging unit

Use the TYPE C input to charge the unit. Make sure the power source is at least 5V/2A, if less, it will take longer to charge. With the correct