



product bulletin

X-Treme Box™

When there's a job to do...there's no time to fool around with power!

Coleman Cable's X-Treme Box™ provides work-site power distribution that's economical, rugged, and most of all safe! Now available in two versions to meet contractor demands. The new roll cage designs are constructed with a tubular steel frame for added durability and are vertically stackable for easy transportation. The X-Treme Box™ provides jobsites with a portable, reliable power distribution center that withstands harsh jobsite conditions.

Features & Benefits

- OSHA and NEC Compliant, ETL Listed
- Reduces electrical hookup and labor time
- 7 overload protected receptacles, 6 with GFCI protection
- Advanced GFCI technology with open neutral and over-voltage protection
- Several boxes can be run in series before a significant drop in voltage occurs
- Weather-resistant receptacles
- Locking or Straight Blade receptacle models available
- Roll Cage versions stack for easy transport



Application Information

Construction

- Commercial and Residential
- Renovation and Demolition

Institutional

- Conventions and Sports Centers
- Special Events

Entertainment

- Cinema, Stage and Concerts
- Broadcasting

Outdoor Events

- Carnivals and Festivals
- Sporting Events



X-Treme Box™

Part No.	Portable Power Distribution Center	50A Power Inlet	50A Power Outlet	30A Power Outlet	20A Power Outlets	Overload and GFCI Protection	Wt Lbs.
01950*	NEMA Type 1 Sled Base	50A 125/250v Locking	50A 125/250v Locking	30A 250v L6-30R Locking w/cvr	(6) 20A 125v L5-20R Locking w/ cvrs	50A - None 30A Circuit Breaker Protected 20A GFCI Circuit Breaker Protected	34
01960*	Rainproof NEMA 3R Sled Base	50A 125/250v Locking w/cvr	50A 125/250v Locking w/cvr	30A 250v L6-30R Locking w/cvr	(6) 20A 125v L5-20R Locking w/cvrs	50A - None 30A Circuit Breaker Protected 20A GFCI Circuit Breaker Protected	34
NEW 01962	Roll Cage Model (Electrical specs are identical to part no. 01960)						
01970*	Rainproof NEMA 3R Sled Base	50A 125/250v Locking w/cvr	50A 125/250v Locking w/cvr	30A 250v L6-30R Locking w/cvr	(6) 20A 125v 5-20R Straight blades w/cvrs	50A - None 30A Circuit Breaker Protected 20A GFCI Circuit Breaker Protected	34
NEW 01972	Roll Cage Model (Electrical specs are identical to part no. 01970)						

* Sled Base Model

Power Distribution Extension Cords

Part Number	Description	Std Pk	Wt Lbs.
01918	50ft 6/3 & 8/1 SEOW 50A 125/250v, Marinco	1	27
01919	100ft 6/3 & 8/1 SEOW 50A 125/250v, Marinco	1	54
01938	50ft 6/3 & 8/1 SEOW 50A 125/250v, Hubbell	1	29
01939	100ft 6/3 & 8/1 SEOW 50A 125/250v, Hubbell	1	57

Replacement Ends/ Adapters

Part Number	Description	Std Pk	Wt Lbs.
05974	50A 3-Pole/4-Wire 125/250v Male, Marinco	1	2
05975	50A 3-Pole/4-Wire 125/250v Female, Marinco	1	2
05958	50A 3-Pole/4-Wire 125/250v Male, Hubbell	1	2
05959	50A 3-Pole/4-Wire 125/250v Female, Hubbell	1	2
01920	6/4 SEOW 50A "Y" Adapter	1	4

X-Treme Stack!



Roll Cage Model



Sled Base Model

